

Model 'BF' Profile Nipple

The Performance Oil Tools, Inc. Model 'BF' Profile Nipple is a Top NoGo or Selective Profile Nipple that allows installation of various wireline flow control devices in the production string.

The location and number of Model 'BF' Profile Nipples should be carefully considered in the completion planning stages to allow maximum versatility in the positioning of various flow control accessories.

FEATURES/BENEFITS:

- Internal sealing bore
- Accepts Selective or Top NoGo Locks
- Multiple Model 'BF' Nipples with the same seal bore can be run in the tubing when Selective Locks are required
- Available in Alloy and Stainless Steel material

APPLICATIONS:

Model 'BF' Profile Nipples may be used for the following operations:

- Land blanking plugs to shut in well or to test the production tubing.
- Land Velocity type Safety Valves.
- Land equalizing check valves.
- Land circulating blanking plugs.
- Land chokes to reduce surface flowing pressures or to have pressure drops downhole to prevent surface freezing in gas production.
- Land instrument hangers with geophysical devices such as pressure and temperature recorders.

Specification Guide Model 'BF' Profile Nipple

Tubing OD	Nipple		
	Seal Bore	Size*	Min. OD
1.660	1.187	1.18	1.875
	1.250	1.25	
1.900	1.437	1.43	2.109
	1.500	1.50	
2-1/16	1.562	1.56	2.250
	1.625	1.62	
2-3/8	1.781	1.78	2.560
	1.812	1.81	
	1.875	1.87	
2-7/8	2.062	2.06	3.109
	2.250	2.25	
	2.312	2.31	
3-1/2	2.562	2.56	3.687
	2.750	2.75	
	2.812	2.81	

* Other sizes for heavy weight tubing are available on request.

