

Model 'BR' Profile Nipple

The Performance Oil Tools, Inc. Model 'BR' Profile Nipple is a Bottom NoGo Profile Nipple that allows installation of various wireline flow control devices in the production string.

The location and number of Model 'BR' Profile Nipples should be carefully considered in the completion planning stages to allow maximum versatility in the positioning of various flow control accessories.

FEATURES/BENEFITS:

- Internal sealing bores for maximum sealing performance
- Available in Alloy or Stainless material

APPLICATIONS:

Model 'BR' Profile Nipples may be used for the following operations:

- Land blanking plugs to shut in the well or to test the production tubing.
- Land Velocity Type Safety Valves.
- Land equalizing check valves.
- Land circulating blanking plugs.
- Prevent loss of wireline work string in some cases.
- Land chokes to reduce surface flowing pressures or to have pressure drops downhole to prevent surface freezing in gas production.
- Land instrument hangers with geophysical devices such as pressure and temperature recorders.

Specification Guide Model 'BR' Profile Nipple

Tubing OD	Nipple			
	Seal Bore	Size*	NoGo ID	Min. OD
1.660	1.187	1.18	1.135	1.875
1.900	1.437	1.43	1.385	2.109
	1.500	1.50	1.447	
2-1/16	1.562	1.56	1.510	2.250
2-3/8	1.781	1.78	1.728	2.560
	1.812	1.81	1.760	
	1.875	1.87	1.822	
2-7/8	2.062	2.06	1.978	3.109
	2.250	2.25	2.197	
3-1/2	2.562	2.56	2.442	3.687
	2.750	2.75	2.697	

* Other sizes for heavy weight tubing are available on request.

