

Model 'OXN' Profile Nipple

Performance Oil Tools, Inc. 'OXN' NoGo Profile Nipples are designed for use in single nipple installations or as the bottom nipple in conjunction with a series of 'OX' Profile Nipples. The profile nipples have the same packing bore I.D. for a particular tubing size and weight. 'OX' and 'OXN' Profile Nipples are designed for use with standard weight tubing. The 'N' designation is for nogo nipples.

FEATURES/BENEFITS:

- Internal Seal Bore.
- Full-opening packing bore with locking recess at top of nipple and a slightly restricted nogo profile at the bottom designed to keep subsurface slow controls from being run below the tubing intake.
- Available in Alloy or Stainless material.
- Available in Pin x Pin or Box x Pin

**Specification Guide
 Model 'OXN' Profile Nipple**

| Tubing OD | Seal Bore | NoGo ID |
|-----------|-----------|---------|
| 1.900 | 1.500 | 1.448 |
| 2-1/16 | 1.625 | 1.536 |
| 2-3/8 | 1.875 | 1.791 |
| 2-7/8 | 2.313 | 2.205 |
| 3-1/2 | 2.813 | 2.875 |
| | | 2.875 |
| | 2.750 | 2.875 |
| 4 | 3.313 | 3.135 |
| 4-1/2 | 3.813 | 3.725 |

